
NXT 110' REAR MOUNT LADDER

TRUCK #L221142





CHASSIS

- Spartan Gladiator MFD Flat Roof
- Advanced Protection System
- Classic Front Fascia Cab
- 12V DC Multiplex Electrical System w/ Driver & Officer Vista Displays
- Cummins X12 Diesel Engine 565 HP EPA 2021
- Quiet Variable Speed Engine Fan Drive
- Transmission Allison 4000 EVS
- ABS/ATC/ESC Brake System
- Hot Dipped Galvanized Frame
- 18" Painted Severe Duty Front Bumper
- Advanced Climate Control System
- Xtreme Duty Dash
- Durawear Zip Clean Bostrom Seats
- Firetech LED Headlights with Four Lamps
- 224.5" Wheelbase

PUMP AND PLUMBING

- Waterous CSU 2250 GPM Pump
- 500 U.S. Gallon Tank
- Trident Air Primer
- (1) 2.5" Left Side Inlet
- (1) 2.5" Left Side Discharge
- (1) 3" Left Side Discharge
- (1) 2.5" Right Side Discharge
- (1) 4" Master Discharge
- (2) 2" and (1) 2.5" Removeable Speedlays
- (1) 2.5" Front Bumper Discharge
- (1) 4" Rear Inlet to feed Aerial
- (1) 3" Tank to Pump
- (1) 2" Tank Re-fill

Body


- Aluminum Body
- Durable Line-x Compartment Finish
- ROM Roll-up Doors
- Wheel Well SCBA and Fire Extinguisher Storage
- EZ Hose Load located on right side with 1,000' of 5" LDH capacity

- Duo Safety Ladder Package: (1) 24 ft. 2-section, (2) 35'
 2-section, (1) 14' roof, (1) 16' roof, (1) 20' roof, (1) 10' attic, (1) 14' 2-section
- Fire Hooks Pike Pole Storage: (1) 12 ft., (1) 8 ft., (2) 6 ft.
- Dual Turntable Access on Beveled Rear Corners
- Whelen LED Lighting Package
- 10.0 kW Harrison Generator

AERIAL

- 14' stabilizer spread offers 750 lbs. dry/ 500 lbs. wet
- 12' stabilizer spread offers 500 lbs. dry/ 250 lbs. wet
- Outrigger Obstruction Detection Display System
- 4-Section Aerial Ladder Design
- Water flow up to 1,500 GPM at 90 degree angle from ladder centerline, either side for a full 180-degrees sweep
- 36.75" stabilizer stroke offers maximum operating grade up to 20%
- Removable bolt-on Stainless Steel Egress
- 750 pound tip load, up to full ladder extension from -7 to 78 degree elevation.
- Operation on grades with 100% of rated capacity on a slope up to 10.5 degrees





		7 12		
	THIS TRANSMENT IS A CONTROLLED THE TRANSMENT OF YOUR FREE APPROACH OF THE TRANSMENT OF THE	GROUND LADDERS: TWO DUG-SAFETY 26 FT 900 ONE DUG-SAFETY 26 FT 970 ONE DUG-SAFETY 26 FT 970 ONE DUG-SAFETY 26 FT 975 ONE DUG-SAFETY 26 FT 8755 ONE DUG-SAFETY 26 FT 9755 ONE DU	D DOOR OPENING 23.50 x 19.50 h 23.50 x 1	CHASSIS: SPARTA ENGINE: CUMMINS X 15 TRANSMISSION: ALLISON AXLES: 23,000 LB. FRON- MODEL: C34R-110 A WATER/FOAM: 500 / FUMP: WATEROUS GENERATOR: 10 KW HARR
U DOMNING WB CORPTION NAME TO SCALE RIAL DEMO TIP LOAD AERIAL 3-012-0124	MANUAL CONTROL OF YOUR FIRE MEETS THE ROMAN OF YOUR FIRE MEETS THE ROMAN OF YOUR FIRE MEETS THE ROMAN OF THE MEETS THE ROMAN OF THE ROM	T. 1200A 2-SECTION T. 400A 2-SECTION F. 500A 2-SECTION F. 500A 2-SECTION F. 500A 2-SECTION F. 500A 2-SECTION F. 700A 2-SECTION F. 500A 2-S	NT TERIOR DIMENSIONS INTERIOR DIMENSIONS INTERIOR DIMENSIONS 23.5 (25.5	PARTAN GLADATOR PARTAN GLADATOR USS X15 565 HP USS X15 565 HP LISON 4000 EVS LISON 4000 EVS PRONT/54,000 LB. REAR PRONT/54,000 LB. REAR FRONT/54,000 LB. REAR FRONT CSU 2250 GPM HARRISON HYDRAULIC

SPARTAN FIRE, LLC. EPHRATA, PA 17522

LADDER TOWER